Certificate of Location of Government Corner

ID#: 633005 **Description:** W SEC COR 30 31 63 **Date Set:** **County:** Olmsted

Section: 30 **Township:** 106N **Range:** 13W **Monument Description:** Contact County Surveyor for additional information

Reference Ties:

This corner is located by GPS reference stations "WR-4 A & B"

Corner History:

10-1853 Gov't Notes: John Ball, Deputy Surveyor North between 31 and 36. 69.25 chs. Spring brook 4 lks. Wide runs N.W. 80.00 chs. Set post and drove charred stake. Built mound with trench and planted Osage Orange S.E. and apple seed N.E.

7-1857 Thomas Hunter (P. 35 No. 56), County Surveyor, used the corner to set the 1/16th North, the 1/16th East, and the 1/16th South.

6-1863 P.C. Compton Pg. 72 No. 104 shows section corner.

8-3-1977 County Surveyor dug for the corner but did not find anything. Set a C.I.M. over a 1/2" x 2' rod as the corner at double the measure from the W. 1/4 Cor. 31 over the E-W fence at the 1/16th North and at Hunter's prorated measure from 1/4 Cor. 30-31 (as prorated against his measure from 1/4 Cor. 30-31 to the N-S fence at the 1/16th West). The corner came in line with an old fence North. RPs-C.S.D. and spike in 14" Box Elder N.W. 32.14', C.S.D. and spike in 5" Box Elder N.N.W. 56.89', Spike and C.S.D. in 6" Box Elder N.E. 37.9'.

12-1-1980 County Surveyor placed Survey marker sign and post 1 1/2' So. Of Monument.

2-26-2004 County Surveyor did not find monument. Corner now falls in flood control dam pond of WR-4. Set two points (WR-4 A&B) to GPS to use as reference of corner position. Found two prop pins: Vince Fangman property pin 200' west and Tom Ferguson property pin 200' south of Vince Fangman pin.