Certificate of Location of Government Corner

ID#: 633109 **Description:** SEC CEN 31 63 **Date Set:** **County:** Olmsted

Section: 31 **Township:** 106N **Range:** 13W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Stone 20"x4"x22" with 1/2"x38" iron on west side (up 12")

Reference Ties:

The corner falls 11' east of fence north and 3' south of E-W fence
The monument is down 0.5'
County Survey Disk in W side 22" Burr Oak N 65.05'
County Survey Disk in SE side blazed Burr Oak SW 16.65'
Post w/sign 2' north
This corner is located by GPS reference stations "Gamehaven A & B"

Corner History:

7-13-1857 T. Hunter, County Surveyor, (Book A, Page 35, Survey No. 56), used corner and measured 38.92 chains (2568.72') to W 1/4 Corner 31.

9-15-1933 J. Kerr, County Surveyor, (Book 9, Page 5), found limestone and meaured 2568.5' to W 1/4 Corner 31.

7-15-1977 County Surveyor found stone 20"x4"x22" on south side of E-W fence and 11.4' ESE of the corner post to fences E-W-N. Set 1/2"x38" rod on the west side of the stone. RPs - Spike & Disc on SE side blazed Burr Oak ENE 61.7', Spike & Disc on West side 22" Burr Oak N 65.05', Spike & CSD on SE side blazed Burr Oak SW 16.65'

6-11-1987 V. Fangman used computed center at intersecting quarter lines.

10-19-2006 County Survey Crew found 20"x4" stone down 0.5' in good condition and measured its position using GPS. Set post with sign.