Certificate of Location of Government Corner

ID#: 633304 **Description:** S 1/4 SEC COR 33 63 **Date Set:** 11/7/1969 **County:** Olmsted

Section: 33 **Township:** 106N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of E-W twp road and 1' west of fence south
Concrete nail in S side PP #44234 ENE 74.3'
Concrete nail in NE side 10" post SSE 35.7'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes, William Jones; 40.0 set section post and drove stake for quarter section corner. Built mound with trench and planted SE osage orange & NE apple seeds.

5-1872 T. Hunter Pg.198 No.208; Corner gone. Set temp point.

6-1877 T. Hunter Pg.316 No.310; Corner gone, set temp point. 16 west set stone.

7-1907 C. Armstrong Pg.112 B; Found boulder stone

5-21-1952 J. Kerr book 55 Pg. 16 found boulder stone. Set 1/2 steel by its side.

9-3-1965 J. Kerr found nothing, replaced according to previous records. RPs- Center of square bed rail set in fence line NNE 22.95, spud and nail in hub on east side large pp NNW 38.13.

7-1969 J. Kerr removed CIM for road grading.

11-7-1969 J. Kerr reset C.I.M. with stone on south side 5" deep.

4-1976 County Surveyor found rust hole believed to be made from rod set by boulder found 5-21-1952. Found rust hole 3' deep, 2.1N and 4.7 west of CIM. Left spike in hole and referenced. RPs- CSD west side brace post SE 39.68, CSD PP #44234 NE 77.46.

8-22-2005 County Surveyor found CIM down 0.7' in good condition.