Certificate of Location of Government Corner

ID#: 633305 **Description:** S SEC COR 32 33 63 **Date Set:** 11/7/1969 **County:** Olmsted

Section: 33 **Township:** 106N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of E-W twp road, in line with fence south and 1 1/2' west of fence north
County highway disk in CP S 34.32'
County highway disk in CP N 16.0'
This corner is located by GPS measurement

Corner History:

5-1872 T. Hunter Pg.198 No.208; Found stone.

6-1877 T. Hunter Pg.316 No.310; Found stone

7-1907 C. Armstrong; set temp point by line & meas.

5-1952 J. Kerr Bk.55 Pg.16; found stone with junk.

9-21-1963 J. Kerr found limestone and 1/2" steel.

7-1965 J. Kerr; Found stone and junk. Set CIM over pipe & trash. RPs- disc fence post S34.32', fence line E-W S 34.0', femce line E-W N 14.5', disc fence post N 16.0', disc pp WNW 160.8', corner lies in line fence south, corner lies 1.5' west fence north, corner lies 1.0' south and 2.5' east of MN State nail.

7-1969 J. Kerr removed CIM for grading. Set 1/2" rod over original rod below CIM. Set 1/2" rod just east of fence south at 75' and rod at 150' on transit line with corners will reset after grad completed.

11-7-1969 J. Kerr reset CIM . RP- disc in pp WSW 161.0'.

4-1976 County Surveyor at 1/16th east found rod packed in limestone as recorded by Kerr.

8-22-2005 County Surveyor found CIM down 0.6' in good condition.