Certificate of Location of Government Corner

ID#: 633404 **Description:** S 1/4 SEC COR 34 63 **Date Set:** 8/12/1982 **County:** Olmsted

Section: 34 **Township:** 106N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 28' north of centerline of CSAH 16, 1' west of centerline of power poles north and 4' west of short fence south
Punch mark in E end CMP ENE 30.95'
1/2" rod 200.15' South and on line to PK nail in PP #38008
Punch mark in W end CMP WNW 29.89'
County Survey Disk in E side Cottonwood NW 139.49'
County Survey Disk in W side PP #38007 N 24.25'
Sign in PP #38007 24' north
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes: John Ball, Deputy Surveyor West between sections 3 and 34. 40.00 chs. Set post and drove charred stake for quarter sec. Cor. Built mound with trench per instructions. Planted S.E. Osage Orange N.E. Apple seed.

6-1876 Thomas Hunter, County Surveyor, (Old Fieldbook 4, Pages 128-129 and Book A, Page 297, No. 292) "Found by digging in center of road, the remains of old stake, in line with old fence running South--Left stake as we found it." Hunter used the corner to set the center 34, a stake, at intersecting 1/4 lines, and the 1/16 North, a stake, set midway and on line between the center 34 and the N. 1/4 Cor. 34 (see note on correcting the E. 1/4 Cor. 34 and thus these corners).

9-1884 T. Hunter (Book A, Page 392, No. 383 and Old Fieldbook 14, Page 24) "Found remains of old stake in line of old fence running South as described in Survey No. 292. Set stone in its place 18" x 8" x 4" with broken brick and glass around bottom." He used the corner to set the 1/16 South, a stone, midway (19.725 chs.) and on line to the center 3, a quarry stone 18" x 2" x 9" at bottom running to point at top with broken glass around bottom, set at the intersection of the 1/4 lines. He set the 1/16 East, a quarry stone 18" x 9" x 4" running to point at top with broken glass around bottom, midway (19.99 chs.) and on line to the N.E. Cor. 3. He set the 1/16 West, a quarry stone with glass around bottom, midway (20.00&3/4 chs.) and on line to the N.W. Cor. 3.

4-1929 John Kerr, County Surveyor, (Kerr Book 1, Page 22-27) used this corner (No description) to set S. Sec. Cor. 34-35 and the S. 1/4 Cor. 35 on line and at single proportionate Gov't measure (2629.7 1/2 mile) to S. Sec. Cor. 35-36 (boulders and stake found).

1932 County Highway Department (C.H.D. Book 64, Page 73) found stone monument. Measured East to stone monument 2633.8'.

1929 J. Kerr (Kerr Book 3, Page 35) apparently found corner (no description) and "ran line from S. 1/4 Cor. 33 to S. 1/4 Cor. 34." Shows a measure of 2640.1' West to S. Sec. Cor. 33-34, then 2642.3' to the S. 1/4 Cor. 33.

1940 J. Kerr (Kerr Book 20, Pages 62-66) "Dug and found N. 1/4 Cor. 3." Ran line South and found a stone 1293' South at the 1/16 South and an iron stake 2597.11' South at the center 3.

9-1965 J. Kerr (Card and Cert. Filed) found limestone, iron, and wood stake. Set C.I.M. over limestone and stake. RPs- hun west side big pp S28.85', corner lies in center road in line fence running north, corner lies 4' south of direct line.

1968 J. Kerr (Kerr Book 101, Page 9-10) shows stone at the corner.

4-7&16-1976 County Surveyor dug with backhoe to remove the C.I.M. for road grading. Found the C.I.M. to be set over the wrong stone. Found Hunter's 4" x 8" x 18" limestone and bricks and glass .9' West and .35' North of the C.I.M. Set a 3/4" x 15" rod for the corner over the stone and took references. The 1/16 West falls in I-90 and the 1/16 East in cut in road.

6-23-1982 County Surveyor found a 1/2" pipe with plastic cap with RLS #6507 in place at the corner. The road here has been regraded since finding Hutner's stone in 1976.

8-12-1982 County Surveyor removed the pipe found 6-23-1982 to set a cast iron monument as the corner from references taken 4-16-1976

9-19-1992 County Surveyor found CIM in good condition 28' north fo centerline CR 16.

8-22-2005 County Surveyor found CIM down 0.5' in good condition. Set sign in PP.