Certificate of Location of Government Corner

ID#: 633505 **Description:** S SEC COR 34 35 63 **Date Set:** 9/20/1995 **County:** Olmsted

Section: 35 **Township:** 106N **Range:** 13W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls 10' north of centerline of CSAH 16
Ref pipe N 61.28'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes, William Jones; 80.0 set post & drove stake in corner to section 2-3-34-35. Built mound with trench, and planted osage orange SE and apple seed SE.

9-1884 T. Hunter Pg.392 No.383 found stone in center of road claimed as where original stake stood.

4-1929 J. Kerr Bk.1 Pg.26; Set SW 35 a stone 3x7x2' with cross. Placed stake by stone.

1936 county highway department Bk.64 Pg. 73 & 75; found stone.

11-1963 J. Kerr found corner. Set CIM over stone boulder with cross. RPs- spike in south pile of RW tressel in 2nd pile west of east bridge abutment or terminal easterly 283.9', disc corner fnece post N10°E 30.8', disc in tele pole S 51.85', corner lies north of north edge of traveled road in ditch as road curves southeasterly.

4-1976 County Surveyor removed Kerr's CIM.

9-1991 County Surveyor set 1" square pipe w/cap at prorated T.Hunter position between S1/4 corner & 34 & S1/4 35 106-13 abd N-S position from sec. Corner 2,3,10,11 105-13. RPs- centerline field drive north, west 22', centerline CR 16 Sly 10 1/2', new fence line north, west ± 22'.

6-1995 County Surveyor found 1" square pipe w/cap 10' north of centerline. Set 1" ref pipe 70 1/2' north of centerline CR 16 in line of fence north.

9-20-1995 county highway department set 1" square pipe w/cap at surface from 1995 referenced location.

10-7-2004 County Surveyor found 1" square pipe w/cap at surface in good condition.

8-22-2005 County Surveyor found 1" square pipe w/cap at surface in good condition.

4-3-2006 County Surveyor found 1" square pipe w/cap at surface in good condition.

4-13-2007 WHKS & Co. found monument in good condition.