Certificate of Location of Government Corner

ID#: 633604 **Description:** S 1/4 SEC COR 36 63 **Date Set:** 9/5/2007 **County:** Olmsted

Section: 36 **Township:** 106N **Range:** 13W **Monument Description:** 1" square pipe w/cap RLS #42638

Reference Ties:

The corner falls 2' south of centerline of TH 52, 73' west of centerline of twp road north and in line with fence south
County Survey Disk in SW side PP #50457 NW 82.76'
This corner is located by GPS reference stations "Doc A & B"

Corner History:

9-1853 Gov't Notes John Ball, Deputy Surveyor; West between sections 1 & 36 40.0 set post for 1/4 corner. RPs- 9" burr oak N76°E 71 links, 12" burr oak S35°W 134 links.

7-1876 T. Hunter Pg.301 No.396; Set boulder stone in ground avered by F.Kinney that he and others set it in place of gov't stake.

4-1892 T. Fraser Pg.475 No.454; Found boulder.

6-1903 C. Armstrong Pg.63 B; Found stone boulder 10x10x12 1' north of corner post. Also found 5x15 limestone S40° 10'E 7 1/2 links from limestone believed strongly to be true corner. However, used boulder as corner.

6-30-1969 J. Kerr; corner came in line fence south, 1.9' south center pavement. Corner lies 70' west of centerline road to north. RPs- Edge of hwy RW POT post NW 52.05, punched cross in road north NE 91.5.

1-12-1976 Keith Ewers; Corner 73' west of centerline of road north.

4-1977 County Surveyor found P.K. nail in bituminous surface over concrete TH 52.

9-16-2003 County Surveyor looked for pk nail but did not find. Punched cross in road North now gone, other tie ok.

9-5-2007 County Surveyor found chiseled cross in concrete down 0.5' in good condition. Drilled through concrete and set 1" square pipe w/cap at surface.

7-14-2009 County Surveyor fouind 1" square pipe w/cap at surface in good condition. Lowered pipe and set new cap down 0.6'.