Certificate of Location of Government Corner

ID#: 640206 **Description:** 1/4 SEC COR 2 3 64 **Date Set:** 9/20/2007 **County:** Olmsted

Section: 02 **Township:** 106N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

County Survey Disk in NW side PP SW 1.25'
County Survey Disk in S side 24" Elm ESE 8.35'
SW corner building extension NE 107.8'
Sign on PP 1' SW
This corner is located by GPS reference stations "Fleming A & B"

Corner History:

1853 Yerby - Gov't Notes 40.00 Set a temp. sec. Post south between sec. 2&3. 39.82 Burr Oak 24N 41W 25' lks. Burr Oak 10 S 4 F lks., Set section post.

1936 J. Kerr found limestone.

5-11-1989 County Surveyor found 1" pipe

7-1-1993 County Surveyor found limestone with + in top 0.33' east and 0.10' north of pipe shot in 1989. Stone has 6"x6" square top.

1-8-1997 Mn/DOT note from corner maintenance record:

This corner was recovered and ties were verified and/or re'established if not in place.

4-19-2002 Mn/DOT survey crew found 6"x6" flat top limestone in good condition down (0.2').

10-11-2002 County Surveyor found 6"x6" stone with chisled "X" down 0.2' in good condition.

9-20-2007 County Surveyor found stone with chiseled "X" down 0.2' in good condition, took local ties and removed. Set 21" CIM at surface from local ties. CSD in S side of 24" Elm ESE 8.35' CSD w/nail in NW side of PP SW 1.25', did not check ties to building.

3-22-2010 Ken Manahan, Mn/DOT Crew Chief, found CIM at surface in good condition.