Certificate of Location of Government Corner

ID#: 640209 **Description:** SEC CEN 2 64 **Date Set:** 11/29/1977 **County:** Olmsted

Section: 02 **Township:** 106N **Range:** 14W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

County Surveyor recommends using the monumented center of section.

1/2" rod

Reference Ties:

The monument is down 0.4'
North side of pipe of gate to ballfield (inside fence) West 64.3'
Punch hole & "X" in SE corner concrete base in flood light NNE 109.00'
Punch hole & "X" in SE corner concrete base in flood light WSW 120.19'
County Survey Disk in post for scoreboard NW 68.1'
This corner is located by GPS measurement

Corner History:

11-6-1855 Robert Mooers used stone for the Original Plat of Rochester.

4-28-1857 Thomas Hunter found and used monument for the plat of Head & McMahon's Addition.

4-8-1869 George Healy used center for the plat of Williams' Healy's & Cornforth's Addition.

9-21-1876 Thomas Hunter, County Surveyor, (Old Field Book #4, Pages 156-159) found monument and measured 218' 5" (218.42') west to stone found at the SW Corner of Block 7, Head & McMahon's Addition.

1888 Thomas Hunter, County Surveyor, states in a report to the Common Council of the City of Rochester that he set a 5"x6"x24" stone at this corner in order to preserve, perpetuate, and more readily define lines.

5-17-1933 Minnesota Highway Department found and used stone for Right of Way Map No. 170-30B.

6-13-1936 John Kerr, County Surveyor, (Kerr Field Book #11, Page 44) found limestone.

1975 City of Rochester Engineer's Department found limestone. RPs - Punch Hole & "X" in SE corner concrete base in flood light NNE 109.00', Punch Hole & "X" in SE corner concrete base in flood light WSW 120.19'

11-29-1977 County Survey Crew found spike from RPs provided by City of Rochester's Engineer Department. Removed spike and found 5"x6" topped limestone with cross down 1.3' in good condition. Found pieces of iron and a chain around the stone. Set 1/2"x12" rod over stone. The corner falls in the outfield of a softball field.

4-19-1989 County Survey Crew found 1/2" rod in good condition. Used in City of Rochester mapping project survey.

5-3-1995 McGhie & Betts, Inc. found and used rod.

10-4-2002 County Survey Crew found 1/2" rod down 0.4' in good condition and measured its position using GPS.

3-31-2010 Brian Veronen, Mn/DOT LSIT, found 1/2" rod down 0.4' in good condition.

11-3-2011 Joel Thoreson, County Surveyor, recommends using the monumented center of section based on historical use of this position.