Certificate of Location of Government Corner

ID#: 640306 **Description:** 1/4 SEC COR 3 4 64 **Date Set:** 6/17/1964 **County:** Olmsted

Section: 03 **Township:** 106N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in backyard of house #802 23rd Ave SW
Blaze in 16" White Oak S 7.0'
Post w/sign 1' south
This corner is located by GPS reference stations "Scarecrow B & C"

Corner History:

7-1854 Gov't Notes W.B. Yerby, Deputy Surveyor S0°W between sections 3 and 4 39.80 chs. Set a quarter section post. 10" White Oak S8°45'E 20 lks. 10" White Oak S30°W 12 lks. 79.80 chs. Section corner.

9-1857 Thomas Hunter (Pg 37, No. 59) Shows quarter post measured east 40 chs. to center of section.

10-1892 Thomas Fraser, County Surveyor (Pg 495, No. 468) Found the marked quarter post which agreed with quarter post. Set stone with marked stake in place of quarter post found. Chained East 10.09 found stake then 10.09 then 20.18 chs to center of section 3. Chained North 19.81 1/2 set sixteenth stone then 19.71 1/2 to section corner.

1919 C.H. Armstrong plat of Hillcrest Sub. shows two bearing trees. White Oak S10°W 7.3' and 7" White Oak East 27.6'.

6-1949 John Kerr, County Surveyor (large John Kerr Bk, Pg 27). Used corner measured North 1323.0 to 1" pipe at sixteenth corner then 1264.8' to section corner a 3/4" pipe measured east 528 then 784.2 to sixteenth corner then 1312.2' to center of section 3.

6-1964 John Kerr, County Surveyor (cert. filed) 1" pipe in place many years. Set C.I.M. over 1 1/2" x 12" pipe in place of 1" pipe.

10-5-1978 Roger Brand, County Surveyor, probed for stone set by Thomas Fraser.

9-18-1989 County Surveyor found CIM in EW fenceline in backyard of house, woods to the south, set sign and post 1.0' south.

10-3-2002 County Surveyor found CIM up 0.1' in good condition.