Certificate of Location of Government Corner

ID#: 640709 **Description:** SEC CEN 7 64 **Date Set:** 11/1/1977 **County:** Olmsted

Section: 07 **Township:** 106N **Range:** 14W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
Cast Iron Monument

Reference Ties:

The corner falls in cultivated field 185' west of N-S row of large pines on west side of farm buildings
Iron set by McGhie & Betts is 280.5' north of the CIM
This corner is located by GPS measurement

Corner History:

12-10-1857 T. Hunter Pg. 40 No. 62, 1/16N 19.52 chains M&L to 1/4 post, measure south 39.50 chains to 1/4 post, measure west 38.06 chains to 1/4 post.

5-24-1871 T. Hunter P. 185 No. 196 set stake at inters. Lines. Measure west 38.16, measure north 39.24, measure east M&L 20.341/2, 1/16 north reset (P. 413 No. 402), 16 south M&L 19.93 (1315.38).

3-1911 C. Larson P. 148 B set iron, stake as corner, north set iron stake (19 rods, 16 lks.), measure east 40.25, measure west 39.30, measure north 39.25.

1945 county highway department B. 159 P. 72, Show measure from center 7 to 1/16 corner south 1318.9 R 1315.38.

1-1953 McGhie - 1/2" rod as corner; hub on south side stump in west yard fence NE 288.7, hub about 94.5' north of SW corner fence.

10-24-1977 McGhie & Betts set 5/8" rerod.

11-1-1977 County Surveyor found McGhie Iron, set CIM over rod set by McGhie. Corner in field 185' ± W of N-S row of pines. Set 5/8" rod 10' south of centerline of Co. Rd. 25 as transit tie; Rt 1/16 south of west 1/4 7 to center 7 of 83° 44' 24" for 1326.06.

11-4-1977 McGhie & Betts set iron 280.5' north of the CIM.

8-16-1996 McGhie & Betts found and used CIM.

4-9-1997 McGhie & Betts found and used CIM.

1-27-2000 McGhie & Betts found and used CIM.

2-11-2002 County Surveyor found CIM down 0.9' in good condition.