Certificate of Location of Government Corner

ID#: 640904 **Description:** 1/4 SEC COR 9 16 64 **Date Set:** 7/21/76 **County:** Olmsted

Section: 09 **Township:** 106N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 3' north of centerline of E-W twp road
County Survey Disk in E side PP NW 31.40'
County Survey Disk in 10" Pine NE 47.20'
Iron pin N 26.84'
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes - W.B.Yerby, East Random 9-16, 40.00 set temp section post west between section 9&16 course 9°09' E. 39.95 set a temp section post in mound of earth, charcoal trench, pits, and planted Osage Orange seeds N&S.

1-1858 T. HunterPg. 47 No. 69, Measure E 39.45 chains to section corner.

12-1893 W. Fraser, P. 539 No. 500 Mr. Cornforth avers Mr. G. Stopple built E-W stone fence just 25' north of stake and fence north in line original stake. Set stone as corner measure west 40.13.

5-1902 W. Fraser, P.38B found stone 25' south stone fence p. 539. 16 south drove iron stake M&L 19.98. RP-5" black oak N12°E 41/2 lks. - cut 3 nicks in tree

7-21-1976 County Surveyor found concrete monument. Set CIM over corner found.

3-4-1977 County Surveyor, 1/16 south found 6"x6" concrete mayo monument under E-W fence. RPs-Spike in E side 19" black oak NNE 19.72, Spike in N side 19" burr oak WNW 10.12.

7-21-1989 County Surveyor found CIM in road under tar patch.

9-30-1999 County Surveyor found CIM down 0.5' in blacktop in good condition.

2-4-2003 County Surveyor found CIM down 0.5' in good condition.