Certificate of Location of Government Corner

ID#: 640906 **Description:** 1/4 SEC COR 8 9 64 **Date Set:** **County:** Olmsted

Section: 09 **Township:** 106N **Range:** 14W **Monument Description:** This corner falls in manmade lake

Reference Ties:

Contact County Surveyor for HARN Coordinate location
This corner is located by GPS reference station "Water Pit A & B"

Corner History:

1854 Gov't Notes W.B. Yerby, 14.60 stream 75 lks. Runs NE, 17.50 enter prairie bottom NE & SW, 40.00 set section post in mound, trench, pits, and planted osage orange seed E&W.

7-1857 T. Hunter Pg. 34 No. 54, 1/16 west 19.95 M&L, 1/16 north 19.77 M&L, total measure shown 39.55 chs.

12-1895 W. Fraser P. 539, No.500 found stake between 2 corner posts described by Hunter as original corner. East drove stake on 1/4 line at 17.507/8 (1155.6' east of W1/4 9) - 16 east in river M&L 20.01.

4-1900 R. Fraser P.664, No. 590 found stake (P.539 & Hunter), North measure to center road 14.60 chains, north (Hunter's overall measure) 39.55.

12-1975 County Surveyor, 1/16 west set 1 1/2" x 24" as corner 2.5' west of fence on E side of N-S road. RPs-CSD on SW side of pp NW 76.91. Spike & CSD NE side of hugh Maple SE 10.7. Corner 2.5 W of fence & 22.8' E of centerline of CR #125.

3-14-1979 County Surveyor at 1/16th west found round mark in clay about 2.8 east and slightly south of pipe. Found 1/2" iron approximately 101/2' S and 11/2' east set by McGhie. Hunter's measure would come 2.91' east of the pipe.

9-5-2007 County Surveyor determined that corner falls in lake.