Certificate of Location of Government Corner

ID#: 641506 **Description:** 1/4 SEC COR 15 16 64 **Date Set:** 10/10/89 **County:** Olmsted

Section: 15 **Township:** 106N **Range:** 14W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls in woods south of house #2512 Crest Ln SW
County Survey Disk in 14" Red Oak SSE 13.91'
County Survey Disk in N side 16" twin Red Oak WSW 7.28'
Post w/sign 1' east
This corner is located by GPS reference stations "Maple & Institute"

Corner History:

7-2-1854 Gov't Notes W.B. Yerby, Deputy Surveyor North between section 15 and 16. 40.00 chs Set a quarter section post and enter thicket and decend hill. Br. Oak 6 in. N54E 190 lks and made trench. RPs-Burr Oak 6N 54E 49°.

11-1872 Thomas Hunter (Pg. 210 No. 218) Found the stake pulled up and lying on the ground. Found the B. tree and old stake hole. Set a stone 2 x 6 x 18. 1/16 E set a stone 2 x 8 x 15 M & L 19.96.

5-1902 W. Fraser (Bk. B Pg. 38) Found a stone as the corner West - 31.15 (2055.9) to a stake in road centerline then 889 to Center Sec. 2642.64 total.

12-1936 John Kerr, County Surveyor (Bk. 12 Pg. 5) Found the conc. monument set in Mayo Survey. 8" Butternut N.W. 11.9' 6" White Oak S80°E 8.5'. RPs- 8" butternut NW 11.9, 6" White Oak S80°E 8.5.

8-1949 McGhie - Rocks in fence line. Original stone or conc. likely in the center R.P.'s. Sp. 15" Blazed Oak N.N.W. 20.7 Sp. 10" Blazed Twin Oak S.W. 7.2 Sp. 8" Basswood N.N.E. 18.2

1968 Forsberg - Found the McGhie corner.

9-21-89 County Surveyor found stone 2" x 6" x 18" standing, packed in stones. Dug down and found no concrete monument as J. Kerr claimed in 1936.

10-10-89 County Surveyor set telspar pipe with C.I.C. in place of stone found 9-21, pipe driven into bedrock.

4-19-2002 Mn/DOT survey crew found monument in good condition.

10-17-2002 County Surveyor found cast iron cap on telspar pipe up 0.4' in good condition.

12-10-2007 County Surveyor found cast iron cap on telspar pipe up 0.4' in good condition.