Certificate of Location of Government Corner

ID#: 641604 **Description:** 1/4 SEC COR 16 21 64 **Date Set:** 3/14/1977 **County:** Olmsted

Section: 16 **Township:** 106N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

County Survey Disk in S side brace post NW 147.13'
1/2" Iron up (3") 6" west of N-S fence and ± 173' south of bracepost with County Survey Disk SW 151.97'
Post w/sign 2' east
This corner is located by GPS measurement

Corner History:

7-1854 Gov't Notes, W.B. Yerby, Deputy Surveyor, West between sections 16 and 21. 40.075 chs. Set a quarter section post in mound of earth and sod and deposited charcoal. Made trench and pits and planted osage orange seed north and south. 80.15 chs. To section corner.

5-1902 William Fraser, County Surveyor, (P. 38B) set a temporary stake midway and on line between the section corners. He set a stone at the 1/16th North, an iron at the Center 16, and an iron at the 1/16th North of the Center 16.

12-1936 John Kerr, County Surveyor, (B. 12 P. 5) set an iron midway and on line.

6-18-1964 John Kerr set a C.I.M. over a 3/4"x12" iron at the location of the iron set in 1936.

3-14-1977 County Surveyor set a C.I.M. over a 1/2"x2' rod midway and on line between the section corners by electronic traverse .23' North and 12.10' west of Kerr's corner (removed). Found a concrete monument at the 1/16th north of the center 16 and Fraser's stone at the 1/16th south of the center 16. The line from the N. 1/4 cor. Sec. 16 over these two corners closely fit the location of the corner as set.

7-1989 County Surveyor found CIM in field (conservation reserve program).

2-8-2005 County Surveyor found CIM down 1' in good condition. Set post w/sign.