Certificate of Location of Government Corner

ID#: 641606 **Description:** 1/4 SEC COR 16 17 64 **Date Set:** 3/14/77 **County:** Olmsted

Section: 16 **Township:** 106N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

County Survey Disk in S side blazed Oak NE 57.44'
County Survey Disk in N side 30" Black Oak E 53.87'
Post w/sign 1' west
This corner is located by GPS measurement

Corner History:

Gov't Notes - 40.00 set section post in mound of soil, charcoal, trench, pits, and planted osage orange seed E&W.

1902's - Fraser used corner 1902 p.38 "B" to set center or some other manner.

12-3-1936 John Kerr B12 P5, Set corner M&L 2637.85. Old buggy axle and shredder feed roll. RPs-Spike in tree 20" NE 57.65. Spike in tree 20" East 53.90.

2-23-1960 Ken McGhie - 1" iron 50' west of fence. RPs-Spike 24" Oak E 53.25. Spike 20" Oak NE 55.22.

3-14-1977 County Surveyor set CIM over a 3/4"x30" rod.

8-10-1989 County Surveyor found CIM in good condition.

2-8-2005 County Surveyor found CIM down 1.2' in good condition.