Certificate of Location of Government Corner

ID#: 641706 **Description:** 1/4 SEC COR 17 18 64 **Date Set:** 3/10/2005 **County:** Olmsted

Section: 17 **Township:** 106N **Range:** 14W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

20d spike in 12" Oak ESE 31.13'
Spike in E side 15" Oak stump SE 5.53'
Post w/sign 2' west
This corner is located by GPS reference stations "Enterprise B & C"

Corner History:

1854 Gov't Notes- W.B. Yerby, 40.00 set section post in mound of earth, charcoal, trench, pits, and planted osage orange seeds E&W.

6-1856 T. Hunter Pg. 9, No. 15, 1/16 north 20.09 chains M&L - Bearing trees (N351/4°E 17 lks.) & (S693/4°E 23 lks.)
1/16 east 19.47 chains M&L to center section, Major breakdown for woodlots in NW 1/4.

11-1857 T. Hunter P. 39 No. 61 subdivided section - North 19.92 M&L south 19.95 M&L west 20.05 M&L. Set centers NE & SE1/4 S. Corner found and used in recent surveys. Limestone 10" above ground. No ties or measure.

5-1873 T. Hunter P. 219, No. 223 found stub of stake, set new marked stake with Jack Oak. Bearing Trees: N151/2°E 28 lks. J.O. 6", N82°E 151/2 lks. J.O. 4".

3-1898 W. Fraser P. 619 No. 562. Found stake, set stone 4"x9"x24", 16 south set stake with stoned laid around it, M&L 19.83, 16 west set stone M&L 20.041/2.

1965, 1975, 1981 McGhie & Betts - found stone 24"x9"x4" in woods ± 1.0' above ground.

1968 Forsberg (Tom Ferguson) found stone.

5-18-1970 County Surveyor ran line and measure from CIM at W1/4 18 line 1.9' s N at W1/4 and fill 8.3' N at E1/4, from W1/4 18 east 1254.6 set 1/2" rod then 1328.8 to 11/4x4' pipe set as center on corrected line, then 1323.4 to 1/2" rod set as 1/16 M&L where limestone found 161/2' west on line. 1/4 17-18 a large mossy limestone in deep woods on high ground up 6" ± didn't reference. Could follow blaze to corner, Rp to 1/16 corner section center 18. This 1/4 17-18 should be CIM & have big iron post as witness.

3-8-1977 County Surveyor found limestone. RPs-Spike in north side 13" black oak ESE 31.09. Spike in east side 12" black oak SSE 5.55.

1-22-1990 County Surveyor found stone, 15" Oak SSE, now a stump.

2-8-2005 County Surveyor found stone up 1' leaning north.

3-10-2005 County Surveyor removed stone and set 4' telspar from ties in trees up 0.4' 20d spike in Oak stump SE 5.53' and 20d spike in north side of 10" Oak ESE 31.13'. Other tie destroyed, tree down. Set sign and post 2' west.