Certificate of Location of Government Corner

ID#: 641806 **Description:** W 1/4 SEC COR 18 64 **Date Set:** 10/19/2000 **County:** Olmsted

Section: 18 **Township:** 106N **Range:** 14W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls in centerline of CR 104 and 10' south of centerline of driveway east at mailbox #2520
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes - W. Yerby - 40.00 set section post, built mound, trench & pits.

11-1857 T. Hunter Pg. 39 No. 61, Measure east 39.12 chains to center section 18.

3-1858 T. Hunter Pg. 50 No. 73, 1/16 east 19.12 chains then 20 chains to center section, 1/16 north 19.78 chains M&L to section corner, (See survey for breakdown & bearing trees of NW1/4 section 18).

11-1891 T. Fraser P.461, No.445, found stone set by Hunter (unrecorded) P. 39 & P. 50 No. 73,
1/16 east set stone 4"x13"x24" with cross on top set on line center 18 - Gov't recorded 38.88 actual 39.131/4 prop give. 19.001/4 then 20.123/4 to center 18 stone 3"x6"x16" with + on top reset from Hunter's stone & stake.

5-1912 Williams P. 168B, didn't use corner, but found stone momument at 1/16 east and center section 18. North of above 1/16 to 1/16 on section line north. Set stone 1311.0 then 1329 to stake set as 1/16 on section line which was replaced by stone.

1945 county highway department B 159-160, has nail 135.3 east P1 curve ?

10-1968 Kerr, Found stake very near M&L. Set CIM M&L 2631.65, McGhie nail in square redwood corner post NE 54.8, county disc in SW side pp #8041 SE 48.55, disc in tele pole 374-1 SW 56.9, disc in black tele pole 374-A-6 NW 56.9, corner lies south center line distant county raod W. Corner lies west centerline north-south road.

9-28-1977 County Surveyor found 2' fill on 2' rock on clay.

3-1-1978 County Surveyor set 10" monument over existing J. Kerr CIM.

7-17-1989 County Surveyor found CIM in good condition.

7-19-1996 County Highway Department tied out corner for CR104 grading. Set 1" square pipe w/cap & post & sign 507±N & 110'E of corner. Rt. Top center of silo w/white top most easterly of 3 silosSW to W1/4 cor. 18 323° 23' 19" Hor. 571.92, Removed CIM.

12-1-1998 County Surveyor found 3/4" iron 9" deep in crushed rock C.R. #104 set from 1996 reference tie in good condition.

10-19-2000 County Surveyor set 1" square pipe w/cap at surface from 1996 reference tie.

2-7-2005 County Surveyor found 1" square pipe w/cap at surface in good condition.