Certificate of Location of Government Corner

ID#: 642006 **Description:** 1/4 SEC COR 19 20 64 **Date Set:** 3/11/2005 **County:** Olmsted

Section: 20 **Township:** 106N **Range:** 14W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls on north side of fence post, 3 1/2' west of N-S fence and 29 1/2' north of fence east
12" Black Oak N74° 30' N 21.0'
10" Black Oak S34° 13' N 13.5'
County Survey Disk in W side twin Maple up 1 1/2' SSW 25.73'
Post w/sign 2' north
This corner is located by GPS reference stations "Cromer A & B"

Corner History:

1854 Gov't Notes - Yerby, 40.00 set section post in mound of soil, charcoal, trench, pits and planted osage orange seeds E&W.

6-1889 W. Fraser P. 627, No. 568 J. Garvey, M. Warren, No evidence of corner. Set stake M&L 39.76 (2624.16), 16 north set stake M&L 19.88.

4-1923 J. Kerr B-8 P.5 P.390 B C.H. Mayo, Set boulder with + at fence corner post on Fraser's stake. Stone 15" long. Set M&L 2625.4 (2624.16). Measure west 2653.0 to center 19. 16 north found Fraser's stake, set stone. Found Fraser's stakes at 1/4 & 1/16 No. on line & porp. Distance, 16 center NE1/4 19 set stone M&L 1328.25 on E-W 1/16 line.

1-1987 McGhies found stone with cross on top.

2-5-1990 County Surveyor found stone with + on top.

3-11-2005 County Surveyor found stone up 0.3', took local ties and removed. Set 2 1/2' telspar w/CIC up 0.5' driven to refusal. Must be another stone below one set in 1923 by Kerr. CSD w/conc nail in west side of twin Maple up 1 1/2' SSW 25.73'. Set sign & post 2' north.