Certificate of Location of Government Corner

ID#: 642209 **Description:** SEC CEN 22 64 **Date Set:** 8/29/2007 **County:** Olmsted

Section: 22 **Township:** 106N **Range:** 14W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls 1' east of centerline of CR 147 and in line with fence east
1/2" rod as property corner E 33.0'
County Survey Disk in SE side PP #16019 SW 65.29'
This corner is lcoated by GPS reference stations "Hart Farm A & B"

Corner History:

12-21-1874 T. Hunter, P. 266 No. 264 set marked stake at intersection of all 41/4 corner, measure north 39.83 = 2628.78, Measure south 40.03 = 2641.98, Caption 9-1886 set stone in place of above stake.

6-1902 W. Fraser P20B found stone (P. 266), 16 west set stone M&L 19.90 = 1313.4 to stone set.

4-1905 C. Armstrong P90B measure south 39.94 = 2636.04, Corner found and used numerous surveys as 11/2" pipe.

9-21-1949 J. Kerr Bk. 43 P.31, Found center Section 22, placed 2" pipe and ran random line south 2637.1, measure to S1/4 22.

4-1954 J. Kerr, Bk. 57 P. 68, Found 11/2" pipe down 7". RPs-Spud in tele pole WSW 31.62. Spud in power pole NNE 59.85.

8-22-1963 J. Kerr set CIM at pipe location.

1976 McGhie & Betts - measure east 2630.44.

8-1-1985 McGhie & Betts found and used Pk nail

7-6-1989 County Surveyor found Pk at surface.

7-11-1989 County Surveyor found spike under Pk, found 5/8" rod.

7-21-1989 County Surveyor found no CIM, set smooth rod at location of 5/8" rod found.

7-12-1994 McGhie & Betts found and used 5/8" iron.

7-1-1999 GGG found and used 5/8" iron.

11-21-2000 McGhie & Betts found and used 5/8" iron at center of section 22.

12-9-2002 Land Consultants used computed position.

2-4-2003 County Surveyor did not find 5/8" iron, presumed destroyed by construction of water main line under CR 147.

8-29-2007 County Surveyor set 1" square pipe w/cap at surface from GPS and traverse data.