Certificate of Location of Government Corner

ID#: 642306 **Description:** 1/4 SEC COR 22 23 64 **Date Set:** 6/16/1964 **County:** Olmsted

Section: 23 **Township:** 106N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls at intersection of fences west and north
20d spike in 16" blazed Red Oak NNE 27.7'
County Survey Disk in pole S 4.79'
Post w/sign 1' north
This corner is located by GPS reference stations "10-36 & 11-36"

Corner History:

1854 Gov't Notes, Yerby, 40.00 set post to section corner with trench. RPs-Burr Oak S 88°E 200 lks.

5-1874 T. Hunter, P.250, No.251, found piece of old stake in mound. Checking from Bearing Tree standing, drove new stake. 16 east set stake 19.89 M&L; 16 center NW1/4 23 set stake at inters of
N-S 1/16 line and line from 1/16 east south of NE 23 over 1/16 So. Of N1/4 23. 19.91 from this corner south to 1/4 line.

4-1901 W. Fraser P.8 B found red cedar post set in place of stake. Measure north 39.63'.

9-21-1949 J. Kerr used E1/4 22, measure south 2650' set 1/16 corner 1325'. Run line between N1/2 & S1/2 of SE1/4 22 - measure 2620.5.

6-16-1964 J. Kerr set CIM over 3/4"x12" rod in place of cedar post. Corner lies at inter of 4 way fences. Lines run and measure south, west & north since 1950.

9-20-1989 County Surveyor found CIM on south edge of woods.

8-15-2001 Mn/DOT survey crew found CIM in good condition.

10-24-2002 County Surveyor found CIM in good condition.