Certificate of Location of Government Corner

ID#: 642404 **Description:** 1/4 SEC COR 24 25 64 **Date Set:** 10/2/1980 **County:** Olmsted

Section: 24 **Township:** 106N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1.9' NE CP to fences E-W-N
Sign on CP 2' SW
This corner is located by GPS measurement

Corner History:

Gov't Notes - Yerby - 40.00 set temp post, west on true line between sec. 24&25, 9° 21'E. 39.95 set a section post in mound of earth, made trench and pitts, planted osage orange E&W of trench.

5-1895 W. Fraser P.566 No.519 Caption 10-28-1901 found mound with stake & stones. 16 west drove stake M&L 19.82 (1308.12' to SW corner 24 stake in lot of small stones.

1941 J. Kerr Book 25 P.18-20 = N1/4 25. Limestone in center of boulders, 11/2" pipe driven by side - about 2' north of post.

10-2-1980 County Surveyor found 11/2" pipe up 1' on East side of 3"x5"x12" limestone. Removed pipe, dug out stone, found nothing else. Set a CIM over a 1/2" iron at stone location. Pipe stood .25E of the center of the stone. Set stone on the north side of CIM.

8-2-1989 County Surveyor found CIM in good condition. Used in City of Rochester mapping project survey.

8-16-2001 Mn/DOT survey crew found CIM in good condition.

10-9-2002 County Surveyor found CIM at surface in good condition.