Certificate of Location of Government Corner

ID#: 642705 **Description:** SEC COR 27 28 33 34 64 **Date Set:** 6/15/1964 **County:** Olmsted

Section: 27 **Township:** 106N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

9" blazed Burr Oak from blaze SSE 8.9'
12" blazed Burr Oak from blaze NE 3.8'
10" blazed Cherry twin SW from blaze 12.7'
14" blazed Burr Oak from blaze NW 17.1'
Center 8" Burr Oak S 27.0'
Center 16" Burr Oak S 34.0'
Post w/sign 2' north
This corner is located by GPS reference stations "Teak Wood B & C"

Corner History:

1854 Gov't Notes- W.B. Yerby, 80.00 set post. RPs-Burr Oak 12N 48W 46 lks. Aspen 12N 23E 94 lks.

5-1875 T. Hunter P.274, No.272 found stake and NW bearing tree standing 16" burr oak, N441/2°W 38 lks. (No description of corner set),
16 east set temp stake M&L 19.881/4. 16 south set temp stake M&L 19.98. 16 north set temp stake M&L 19.983/4.

6-1903 C. Armstrong P.64B shown stake avered by Mr. Richards as corner. Ran line SE 27, found stake at 1/16 west of SE 27. Reran line west and found true corner (160 lks. North). Set limestone 2x12x15 with bearing trees - 7" burr oak S 40° W 45' links (29.7'), 8" burr oak NE 261/2 lks. 17.5' measure east 79.60, but 1/16 mentioned lay 6" south of straight line.

1958 J. Kerr found stone, measure west 2661.95 M&L.

1960 J. Kerr found stone, measure north 1317.87 M&L.

6-15-1964 J. Kerr set CIM over 3/4" x 1" rod.

8-4-1972 County Surveyor found CIM, set up traverse from corner NE'ly to open area then direct to 26-27-34-35 by electronic 5245.64.

6-22-2005 County Surveyor found CIM up 0.3' in good condition.

7-6-2005 County Surveyor found CIM up 0.3' in good condition. Set post w/sign.