Certificate of Location of Government Corner

ID#: 642809 **Description:** SEC CEN 28 64 **Date Set:** 6/16/64 **County:** Olmsted

Section: 28 **Township:** 106N **Range:** 14W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
Cast Iron Monument

Reference Ties:

1" pipe some above ground S 0.6'
County Survey Disk in N side 24" Oak W 38.19'
Sign on fence post
This corner is located by GPS reference stations "Orth A & B"

Corner History:

6-20-1856 T. Hunter, Pg. 11, No. 17, Bearing tree's to center (N521/4°E 191/2 lks.) & (N243/4°W 50 lks.) (S 191/4°W 27 lks.) (S 37°E 21 lks.) Survey of E1/2 NW1/4 & W1/2 NE1/4. 1/16 W 19.58 chs. 1/16 E 20.04 chs. Measure north 40.18 chs. N-S 1/16 line in NW1/4. Measure 39.81 chains, N-S 1/16 line in NE1/4 measure 39.82 chains.

12-17-1957 J. Kerr, B.66, P.68, set center at inter lines, a pipe, Set 1/16 rod W 1326.07 M&L. Set 1/16 rod E 1320.35 M&L. Measure south 2637.67.

6-16-1964 J. Kerr set CIM in place of pipe. Corner shifted from pipe set in 1958.

10-3-1989 County Surveyor found CIM.

7-11-2005 County Surveyor found CIM in good condition at surface. Monument falls along west side of westerly of 3 wooden fence posts. CSD with concrete nail in north side of 24" Oak west 38.19'. Set sign on fence post. Trees used for ties are gone 1" pipe still there.

8-15-2007 County Surveyor decided to leave CIM as final position of center of section 28.