Certificate of Location of Government Corner

ID#: 642909 **Description:** SEC CEN 29 64 **Date Set:** **County:** Olmsted

Section: 29 **Township:** 106N **Range:** 14W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
Limestone

Reference Ties:

Center 30" Oak E 4'
Post w/sign 1' east
This corner is located by GPS reference stations "Moline C & D"

Corner History:

5-30-1877 T. Hunter P.314, No.308 S29 - Set stake at true inters lines. 16 north set stake M&L 19.86. 16 center NW1/4 set stake inters line. 16 west set stake M&L 20.103/4. 16 south set stake M&L 19.91. 16 center SW1/4 set stake M&L 19.88 N-S 1/16 line. 16 center SE1/4 set stake inters lines.

5-21-1895 W. Fraser, P.572 No.524 S29 Thomas Coleman - found bottom stake set P.314 drove new stake well down flush with surface. 16 east didn't find old stake, set new stake stone by side (1322.31 M&L 20.031/2). 16 south found stake P.314 found it M&L 19.91 (1314.06) set iron stake with boulder by its side. 16 center SW1/4 set stake with stone by its side M&L 19.88 on N-S 1/16 line. 16 west found stake P.314. Found it M&L 20.10 1/2. Set new stake with stone by side.

4-1919 C. Armstrong, P.305, stone marked on plat. 16 north iron stake on plat M&L 1318, 2-rod cartway apparently centering on E-W 1/16 line east thru center of NE1/4 29.

8-19&26-1970 County Surveyor this corner a key one in relocating the N1/4 29 for county grading operations. Finally found perfect limestone corner after digging several times from measurements found 1/16 stone and iron south of center and found S1/4 29 to be in error. Measure S1/4 29 north 1313.93 R1314.06. Measure 1/16 to center on brush offset east 1312± rather short to limestone found 1' SW of corner post. To test corner offset 75' at E1/4 29 and 1/16 fence west of E1/4 29 as it goes east and center stone. Accepted center as true corner.

9-23-1987 Kleinschmidt Surveying found and used limestone.

10-11-1989 County Surveyor found 3/4" rod, post with county surveyor sign missing 1.0 east fences N-S-W.

3-11-2004 County Surveyor found 3/4" iron rod that was found previously also discovered two other 3/4" iron rods on the south & east, also found 1/2" iron rod to the north, 3/4" iron rod found before was on west side of limestone that was in the center of the four iron rods down 0.6'. Turned angle to center of limestone, drove all four rods below limestone. Monument falls in NW corner of fences N-S-W.