Certificate of Location of Government Corner

ID#: 643004 **Description:** 1/4 SEC COR 30 31 64 **Date Set:** 3/10/2004 **County:** Olmsted

Section: 30 **Township:** 106N **Range:** 14W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 29' south of centerline of twp road east and 16' east of centerline of twp road north
Post w/sign 2' south
This corner is located by GPS reference stations "Christopherson A & B"

Corner History:

Gov't Notes - 40.00 set temp section post east between section 30&31 N89° 55'E. 38.60 set a quarter section post. RPs-Burr Oak 12" N 30E 27 lks. Burr Oak 4" S 44W 21 lks.

6-1859 T. Hunter P.61 No.87 - Used corner set 16N M&L 19.72. Set 16 center SW1/4 30-19.74 from N - 20.0 from east.

6-1877 T. Hunter P.315, No.309 found stake, tested bearing tree stump and drove new stake, no measure, no 1/16 corner.

12-1973 McGhie & Betts, Set 1 1/4" iron rod by Gov't proportionate measure of so line section 30. Measure east 2614.30, west 2522.79 by elec trav.

3-10-2004 County Surveyor found 1 1/4" rod up 0.3' in good condition. Removed rod and set 5' telspar pipe with cast iron cap up 0.2'.