Certificate of Location of Government Corner

ID#: 643009 **Description:** SEC CEN 30 64 **Date Set:** 6/1/1973 **County:** Olmsted

Section: 30 **Township:** 106N **Range:** 14W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
1 1/4" rod

Reference Ties:

The corner falls 6' east of centerline of N-S twp road and in line with fence east
County Survey Disk in PP #42979 WSW 52.36'
This corner is located by GPS measurement

Corner History:

6-3-1859 T. Hunter P.61, No.89 Used center as corner, 16 so 19.74 M&L. 16N 19.81 M&L. 16W 20.0 then 18.20 to W1/4 bearing trees. 16 center NW1/4 20.0 east - 19.80 south. 16 center SW1/4 20.0 east - 19.74 north.

1973 - McGhie & Betts, Set 11/4" rod as center 30, which is 6.0' East of centerline N-S road and 15' N of fence to west. Also, set 1/16 corner N-S.

6-28-1979 Zenk Engineering found and used 1 1/4" rod at center of section 30

6-8-1992 Zenk, Read, Trygstad & Associates used 1 1/4" rod at center.

7-10-1992 V. Fangman found and used 1 1/4" rod at center of section 30.

3-10-2004 County Surveyor found 1 1/4" rod down 0.3' in good condition.

9-30-2005 Yaggy Colby Associates found and used 1 1/2" iron rod at center of section 30.