Certificate of Location of Government Corner

ID#: 643305 **Description:** S SEC COR 32 33 64 **Date Set:** 10/13/1981 **County:** Olmsted

Section: 33 **Township:** 106N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 4' south of centerline of CR 148 and 4 1/2' east of fences north and south
County highway disk in NW side PP #9883 SW 51.16'
County Survey Disk in E side CP SSW 34.78'
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes, M. Karrick - 80.00 set section post for corner to section 4-5-32-33. RPs-Burr Oak 10S 51 East 297 lks. Burr Oak 12S 10W 266 lks.

5-1874 T. Hunter P.252, No.252, found post.

5-1883 T. Hunter P.381, No. 372, found post, left as found, 16 east set stake M&L 19.931/2 (1315.71), 16N set stake M&L 19.931/4 (1315.55). 16 center SW1/4 33 set stone M&L on N-S 1/16 line 19.901/2 (1313.73).

6-15-1964 J. Kerr, E. Dody found iron and stone, set CIM over iron and stone. Corner lies 8' east of fences N&S, a little north centerline road ±, measure west to N1/4 5 County Highway Department corner 8.36.

8-4-1972 County Surveyor found wood stake as recorded at 1/4 32-33 about 1.5' NE'ly of corner fence post. Measure north to 28-29-32-33 2628.1, removed CIM and moved west 8.36 and north 1.44. Measure now N2628.1 R 1883 2631.1. Measure now E 2629.22 R 5-1883 2631.42. 52.9 SW to nail in disc pp, org. RP SW 57.5. 41.9 SE to Root Beer bottle cap on NE side cross back post 265.9± WSW'ly to punch hole south end new road culvert. Measure west to iron placed by county highway department as S1/4 32 2636.14.

10-13-1981 County Surveyor set CIM over a 1/2"x18" re-rod.

10-14-1981 County Surveyor removed old CIM and pipe beneath new corner 5.89 and 3.94 east.

6-24-1986 county highway department found CIM and took ties.

2-13-2004 County Surveyor found CIM down 0.5' in good condition.