Certificate of Location of Government Corner

ID#: 643404 **Description:** S 1/4 SEC COR 34 64 **Date Set:** 7/12/2005 **County:** Olmsted

Section: 34 **Township:** 106N **Range:** 14W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

County Survey Disk in W side twin 12" Oaks SSE 11.42'
Post w/sign 2' south
This corner is located by GPS reference stations "Forest High A & B"

Corner History:

1854 Gov't Notes, M. Karrick - 40.00 set 1/4 section corner with post. RPs-White Oak 14N 70E 38. Black Oak 8S 56W 41.

5-1875 T. Hunter P.274, No.272, didn't go to this corner on original survey.

6-1876 T. Hunter P.299, No.294 found original stake, found stumps of bearing trees which proved corner. Set new stake with old stake beside it. Measure east 39.93 (2635.38' to original stake).

6-1882 Caption - found marked stake (p.299) 16 west set stake M&L 19.941/2 (1316.37'), measure east 39.93 (2635.38') 16 north set stake M&L 20.00. Total mile south line 34 5268.12.

July 1903 R. Fraser FB#10 P.17 drove stake and took witness tree - white oak S12E 9.9', measure "A" to "C" overran 25 lks 16.5'.

11-22-1974 County Surveyor set CIM over 3/4" rod on line by projecting line from north and by prorated measurement south of center 34.

10-27-1978 County Surveyor set survey marker and sign & post 1' east.

6-24-1986 county highway department found CIM.

2-18-2004 County Surveyor found CIM at surface with head broken and leaning. Removed CIM and found 3/4" iron rod down 2.2'.

7-12-2005 County Surveyor found 3/4" iron rod, took local ties and removed. Set 6' telspar pipe w/CIC up 0.6'. Updated ties. Set sign and post 2.0' south.