Certificate of Location of Government Corner

ID#: 643406 **Description:** 1/4 SEC COR 33 34 64 **Date Set:** 11/25/1974 **County:** Olmsted

Section: 34 **Township:** 106N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2' NW of CP to fences N-S-E
County highway disk in twin 6" Oak ENE 15.7'
County Survey Disk in 6" Oak NE 26.25'
Center of 18" Oak NE 18'
Post w/sign 1' NE
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes; W.B. Yerby; 40.0 set a section post. RPs-10" Burr oak N62W 378 links, 8" burr oak N14E 234 links.

5-1875 T. Hunter P.274 No.272 found corner, tested NE Bearing tree, proved correct so left as is. Measure north 39.96 set temp point M&L.

1882 Caption - 16 east set marked stake M&L 19.883/4 (1312.6') 16 center NW1/4 34 found fence corner correct intersecting lines. 16 center SW1/4 34 set unmarked stake at corner, M&L N-S 1/16 line 19.981/2.

5-1883 T. Hunter P.381, No.372 found stake, tested NE Bearing Tree and proved correct, left as is. Measure south on plat M&L 19.97. Bearing tree - 8" Burr Oak N14°E 234 lks. 154.44.

11-25-1974 County Surveyor set CIM over 1/2" rod with boulder on east side of CIM. Corner lies ± 2' NW of present corner post of fences N-S-E.

10-17-1978 County Surveyor set sign and post on NE'ly side of CIM ± 1' away.

7-6-2005 County Surveyor found CIM down 0.1' in good condition.

5-17-2016 County survey crew found cast iron monument at the surface in good condition.