Certificate of Location of Government Corner

ID#: 643604 **Description:** S 1/4 SEC COR 36 64 **Date Set:** 4/11/2005 **County:** Olmsted

Section: 36 **Township:** 106N **Range:** 14W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 33 1/2' south of E-W PP line
County highway disk in PP NW 40.39'
Post w/sign 2' south
This corner is located by GPS reference stations "LQ A & B"

Corner History:

1854, Gov't Notes, Karrick, 40.00 set post and drove charred stake for 1/4 section corner. Built mound and trench, Planted SE osage orange, NE Apple seeds.

6-6-1863 P.C. Comptom, Pg. 72 No.104, 1/16 north set M&L No (meas). Used 1/4 corner to set center 36 at intersecting lines.

11-1907 C. Armstrong, P. 110B, Sections 1,11,12, 105.14 (8 parties used line of fence running south) Mr. Tracy avers original gov't stake stood 33' north of corner of this fence running south, used only to set center section 1.

7-1974 (See drawing on file), County Surveyor dug in this area for the corner and found a very dark spot in the clay. Set 1 1/2" pipe. RPs-175.0' NNE on transit line to Northern Heights water tank, 40.32 disc in pp NW.

7-16-2003 County Surveyor found 1" pipe down 0.6' leaning badly.

7-18-2003 County Surveyor found 1" pipe down 0.8' leaning. 1 1/4" transit tie NNE down 0.1' leaning.

4-11-2005 County Surveyor found 1" pipe down 0.7' leaning. Found boulder stone down 2' and removed. Set 5' telspar pipe w/cast iron cap down 0.1'. Set post w/sign.