Certificate of Location of Government Corner

ID#: 650105 **Description:** SEC COR 1 2 11 12 65 **Date Set:** 9/9/1965 **County:** Olmsted

Section: 01 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1' north of centerline of E-W twp road and 1' west of centerline of N-S twp road
County Survey Disk in PP #8198 NE 37.6'
Center Bell telephone steel post NW 51.62'
This corner is located by GPS measurement

Corner History:

6-1854 Michael Karrick 60.00 enter prairie bears East. 63.05 creek 8 lks wide runs NE. 80.00 set post in mound with trench, pits, charred stake and Osage Orange seeds at each angle for corner to sections 1,2,11 and 12.

5-1879 T. Hunter (P.360 No.351) found stake in center road avered by Montigue and McGovern to be at site of original stake set stone 2 x 7 x 18 (no meas).

4-1902 C. Armstrong (P.34B) found limestone 2 1/2 x 11 x 20 in line fence South in center road North. North side East-West roads. North meas 39.77 with temp point M&L 19.88 1/2 for line E. 1/16 East 3 x 10 x 12 limestone M&L 19.963 to stake found. Stone set. 1/16 center SW 1/4 1 set stake M&L N-S 1/16 line.

4-1965 J.Kerr dug for corner-hit frost

9-9-1965 J.Kerr dug extensively, found stone 2 1/2 x 11 x 20 as recorded 40" below surface. Set CIM over stone with 1 1/4 x 10" pipe riser. Meas East 2635.4 to S 1/4 1 R 2635.2. Meas mile East 5282.3. 1/16 East set 1/2" rod on line to 1/4 corner which lies at 1317.7. S 1/4 1 lies .9' North direct line. 1/16 corner lies 2' North centerline traveled road and is 48.0' South to 3/8' rod up 6" under fence, ball on fence wire. RP's Nail in hub power pole SE side NE 37.6'. Center tele steel bell post NW 51.62'.

8-14-1968 J. Kerr school gone, tele pole gone--disc in P.P. WNW 124.2'

6-1970 County Surveyor dug up corner for use West.

10-23-2000 County Surveyor found CIM down 0.8' in good condition.