Location of Center of Section

ID#: 650309 **Description:** SEC CEN 3 65 **Date Set:** 8/4/2000 **County:** Olmsted

Section: 03 **Township:** 106N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

1" square pipe w/cap RLS #15809

County Surveyor recommends using the monumented center of section

Reference Ties:

The corner falls 1/2' west of centerline of CSAH 3 and 17' north of centerline of field entrance west
The monument is at the surface
Chisel cut in south end 18" CMP SW 46.14'
Pepsi cap in south side power pole WNW 48.87'
Ref pipe WSW 50.57'
This corner is located by GPS measurement

Corner History:

8-10-1857 E.P. Bircher, by John B. Fellows, Deputy, (Old Road Book, Page 72, Road No. 76 and New Road Book, Page 178, Road No. 76), used quarter line for road survey.

5-11-1867 H.E. Horton, County Surveyor, (Book A, Page 83, Survey No. 126), used center. 1/16th South midway and online at 19.98-1/2 chains (1319.01'). 1/16th East midway and online at 20.04 chains (1322.64'). 1/16th Center of SE 1/4 midway and online on east-west sixteenth line at 20.02 chains (1321.32').

5-2-1968 John Kerr, County Surveyor, (Kerr Field Book No. 88, Page 9), set 1/2"x10" rod at intersecting quarter lines. The corner falls in centerline of north-south county road. RPs - Chisel cut in south end 18" CMP SW 46.1', Pepsi cap in south side power pole W 48.05'. 1/16th West set 3/4"x30" pipe midway and online at 1321.2'.

5-2-1979 Zenk Engineering found and used iron monument.

1-14-1981 Thomas Taylor found and used monument.

5-30-1984 County Survey Crew found 1/2" rod.

6-3-1999 County Survey Crew found 1/2" rod. The corner falls 1/2' west of centerline of CSAH 3 and 8' south of line of crooked fence west. Set 1" square pipe w/cap as reference and referenced corner prior to cold recycling bituminous project. Removed 1/2" rod. RP - Ref pipe WSW 50.57'.

8-4-2000 County Survey Crew set 1" square pipe w/cap at surface from references for 1999 bituminous overlay project. The corner falls 1/2' west of centerline of CSAH 3 and 17' north of field entrance west.

6-15-2001 Vince Fangman found and used 1" square pipe w/cap.

1-21-2003 Vince Fangman found and used 1" square pipe w/cap.

12-20-2004 Vince Fangman found and used 1" square pipe w/cap.

11-9-2005 Vince Fangman found and used 1" square pipe w/cap.

7-12-2006 County Survey Crew found 1" square pipe w/cap at surface in good condition and measured its position using GPS.

8-14-2012 WSN found and used monument.

9-1-2015 Joel Thoreson, County Surveyor, recommends using the monumented center of section based on historical use of this position.

6-5-2019 Massey Land Surveying found and used 1" square pipe w/cap.