Certificate of Location of Government Corner

ID#: 650405 **Description:** SEC COR 4 5 8 9 65 **Date Set:** 5/1/1977 **County:** Olmsted

Section: 04 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2' north of centerline of east-west township road (10th St SW) and in line with fence south
The monument is down 0.5'
Center of tree NE 77.2'
Center of tree NE 86.7'
This corner is located by GPS measurement

Corner History:

6-7-1854 Michael G. Karrick, Deputy Surveyor, measured north 80.00 chains between Sections 8 and 9. Set post for corner to Sections 4, 5, 8 and 9. Erected mound with trench, pits, charred stake, and Osage Orange seeds at each angle.

5-21-1873 Thomas Hunter, County Surveyor, (Book A, Page 225, Survey No. 228), found piece of rail in what appeared to have been once a mound. Dug and found two small stakes on each side of it and below all these the remains of a still older stake. Set stake. 1/16th South set stake midway and on line at 19.87 chains (1311.42'). 1/16th East set stake midway and on line at 19.94-1/2 chains (1316.37').

7-1-1873 Thomas Hunter, County Surveyor, (Book A, Page 233, Survey No. 234), found stake. 1/16th East set stake midway and on line at 19.94-1/2 chains (1316.37'). 1/64th East set stake midway and on line at 9.97-1/4 chains (658.19').

5-13-1977 County Survey Crew dug with backhoe and found stake. Set 1/2"x24" rod in stake hole and Cast Iron Monument over 1/2" rod. The corner falls in centerline of east-west township road and 3' east of main line of fence south. RPs - Nail in PP NW 26.2', Center of tree NE 77.2', Center of tree NE 86.7'.

7-16-1980 County Survey Crew found Cast Iron Monument.

5-31-1984 County Survey Crew found Cast Iron Monument.

5-22-2002 County Survey Crew found Cast Iron Monument down 0.5' in good condition and measured its position using GPS.