Certificate of Location of Government Corner

ID#: 650505 **Description:** SEC COR 5 6 7 8 65 **Date Set:** 10/2/2006 **County:** Olmsted

Section: 05 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1-1/2' south of centerline of east-west township road (10th St SW) and in centerline of township road (109th Ave SW) south
The monument is down 0.4'
Bottle cap in NE side PP #8603 NW 50.08'
County Survey Disc in SE side PP #8604 NE 44.16'
Center telephone box post NE 54.65'
This corner is located by GPS measurement

Corner History:

6-9-1854 Michael G. Karrick, Deputy Surveyor, measured north 80.00 chains between Sections 7 and 8. Set post for corner to Sections 5, 6, 7 and 8. RPs - 7" Black Oak S30°W 291 links (192.06'), 7" Black Oak N63°W 251 links (165.66'), 10" Black Oak N23°E 319 links (210.54'), 7" Black Oak S28°E 115 links (75.90').

9-30-1856 E.P. Bircher, by Thomas Hunter, Deputy, (Old Road Book, Pages 19-20, Road No. 20 and New Road Book, Pages 99-100, Road No. 20), used section post for road survey.

8-14-1857 E.P. Bircher, by John B. Fellows, Deputy, (Old Road Book, Page 71, Road No. 75 and New Road Book, Page 177, Road No. 75), used section post for start of road survey.

10-2-1858 H.W. Farrington, (Old Road Book, Pages 141-142, Road No. 93 and New Road Book, Pages 202-203, Road No. 93), used section post for road survey.

6-16-1870 Robert Perry, County Surveyor, (Book A, Pages 126-127, Survey No. 159), corner gone. Set stake at intersection of measure from SW & NE bearing trees. SE & NW bearing trees gone. 1/16th North set stake midway and on line at 20.00 chains (1320.00'). 1/16th West stake midway and on line at 19.90 chains (1313.40').

10-17-1884 Thomas Hunter, County Surveyor, (Book A, Pages 393-394, Survey No. 384), found stake. 1/16th West set stone midway and on line at 19.96 chains (1317.36').

4-5-1894 William Fraser, (Book A, Page 545, Survey No. 505), found stone that had been planted in place of stake. 1/16th North set stake midway and on line at 20.00 chains (1320.00').

7-10-1968 John Kerr, County Surveyor, dug and found 4"x6"/8"x14" stone in cluster dozen smaller stones in clean soil. Set Cast Iron Monument over stone with 5/8"x16" rod below. The corner falls 1-1/2' south of centerline of road west and 2' west of centerline of road south. RPs - Teem bottle cap in PP #8603 50.1', Root Beer bottle cap in PP #8604 NE 44.1', Center telephone box post NE 54.65'.

9-4-1970 Roger Brand, County Surveyor, found Cast Iron Monument.

7-16-1980 County Survey Crew found Cast Iron Monument.

5-7-2002 County Survey Crew found Cast Iron Monument with head broken off down 1.4' in good condition.

10-2-2006 County Survey Crew found Cast Iron Monument with head broken off down 1.5' in good condition. Took local ties and removed. Found stone down 3.1' in good condition matching Cast Iron Monument ties. Set Cast Iron Monument down 0.4' over stone and measured its position using GPS. The corner falls 1-1/2' south of centerline of east-west township road (10th St SW) and in centerline of township road (109th Ave SW) south. RPs - Bottle cap in NE side PP #8603 NW 50.08', County Survey Disc in SE side PP #8604 NE 44.16'.