Certificate of Location of Government Corner

ID#: 650604 **Description:** 1/4 SEC COR 6 7 65 **Date Set:** 6/30/1972 **County:** Olmsted

Section: 06 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 12' south of centerline of E-W twp road and 36' east of east line of PP north
Bottle cap in W side PP NW 159.50'
This corner is located by GPS measurement

Corner History:

6-1854 Michael Karrick 39.18 set quarter section post. Black Oak 7 S 55 W 236. Burr Oak 12 N 55 E 293.

6-1870 R. Perry (P.126 No.159) found stake claimed by all conserned as present location as exact spot of original stake never moved. 1/16 West set stake 19.92 then 19.10. 1/16 East set stake 19.90 then 19.90. 1/16 North set stake 20.00 then 20.00.

10-1884 T. Hunter (P.393 No.384) N.Bale, found remains of old stake after projecting line from N 1/4 6 over center 6 for 40 chs. Stake lies 1 link S and 3 links E of point by projection set. Stone and broken glass in place of stake came on South side of wagon track. 1/16 East set stone 19.96 M&L 1317.36. 1/16 West set stone on line at 19.99 then 19.17 to stone 1265.22 2 x 8 x 24.

4-1894 W.Fraser (P.545 No.505) found stone by Hunter (P.393). 1/16 West found stone. 1/16 North set stone M&L 20.07 1/2. 1/16 center SW 1/4 6 set stake on N-S 1/16 line M&L 19.97.

7-1910 C. Larson (P.134B S.7) found stone with limestone under. States 1/16 West 19.99' then 19.18' to SW cor 6.

10-1930 J.Kerr (B.3 P.30) used corner of set center 7 at true inters lines. Corner likely assumed at that time.

9-21-1970 County Surveyor found stone 1' south of south edge of traveled road. Limestone 4x12x20 badly eroded with boulder flat and round 8x14 round on top.

6-30-1972 County Surveyor found 3/8" iron bent and pushed in soil. Reset corner with CIM over stones below.

5-9-2002 County Surveyor found CIM down 0.6' in good condition.