Certificate of Location of Government Corner

ID#: 650605 **Description:** W SEC COR 6 7 65 **Date Set:** 7/11/1968 **County:** Olmsted

Section: 06 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 6' west of centerline of N-S twp road and 2' south of centerline of E-W twp road
Center of largest twin Oaks SE 114.5'
Center of 24" Elm blazed SE 123'
Bottle cap in PP NW 48.77'
This corner is located by GPS measurement

Corner History:

10-1853 John Ball 80.00 set post and drove charred stake corner to sec 1,6,7 and 12. Built mound of earth and sod. Pit 8 links South.

6-1870 R. Perry (P.126 No.159) set notched stake by fences, 50 lks North of fence running East on South side road and split fences of road running South. 1/16 East set stake on line at 19.10 then 19.92 to S 1/4 stake.

10-1884 T. Hunter (P.393 No.384) found 8" of very rotted stake after meas W 1/4 6 to W 1/4 19 and found 72 lks short. Also SE 6 to 3 miles West of SW 6, satisfied with find set stone 2 x 8 x 24. Dug 6' dia 18" deep. Doubtful if this was Perry's assumed stake, likely genuine original stake. 1/16 East set stone on line at 19.17 then 19.99 to S 1/4 cor. which was old stake found replaced with stone and glass. Meas North 39.77 South 39.88.

4-1894 W.Fraser (P.545 No.505) doubt if corner used. Found 1/16 stone East set 1/16 stake M&L North said. 1/16 cor to 1/16 stone set on EW 1/4 line 19.97' however found 1/4 stone East.

7-1910 Chas Larson (P.134B) found stone with limestone under 2 x 8 x 24. South set iron stake 1' long at 9.94' (656.04) then 29.82' (1968.12) to W 1/4 7 a stone with stone under 2 x 16 x 24, also drove stake 19.18' East of above iron rod.

7-11-1968 J.Kerr meas line from W 1/4 6 and SE cor 6, found recorded stone deep in sub-soil.

5-9-2002 County Surveyor found CIM in good condition down 1'.