Certificate of Location of Government Corner

ID#: 650606 **Description:** W 1/4 SEC COR 6 65 **Date Set:** 5/20/66 **County:** Olmsted

Section: 06 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of N-S twp road and 2' south of fence east
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes: John Ball, Deputy Surveyor; 40.0 set quarter section post. RPs-14" burr oak S 40° E 167 links, 10 " black oak N 27° E 112.

6-1870 R. Perry Pg. 126 No.159; Found old stake standing. Tested 2 bearing trees or stumps(gone). !/16 E set stake at 19.12 1/2 then 19.86 to center 6(set). 1/16 north set stake M & L 19.89.

10-1884 T. Hunter Pg.393 No.384; Found stake Pg.126 center road undesputed. Filed Bk.14 Pg.27. Corner stands nearly a rod east of direct line between section corners. Meas. North 39.82 (Perry 39.78, meas. South 39.77.

4-1894 W. Fraser Pg.545 No.505; Found stake Pg.393 with stone by side. 1/16 east set stone and stake on line at 19.10 then 19.88 to center 6. 1/16 center SW 1/4 6 set stake M & L 19.97 on N-S 1/16 line.

5-20-1966 J. Kerr found stone and stake. Set CIM over 5/8"x2'rod set original stone (8x8x27) on north side as witness, large gray boulder. (limestone)

5-9-2002 County Surveyor found CIM in good condition down 0.5'.