Certificate of Location of Government Corner

ID#: 650609 **Description:** SEC CEN 6 65 **Date Set:** 10/19/1989 **County:** Olmsted

Section: 06 **Township:** 106N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

County Surveyor recommends using the computed intersection of quarter lines for the center of section.

Cast Iron Monument

Reference Ties:

The corner falls 1' west of corner post for fences north-east-west
The monument is at the surface
Sign on corner post 1' east
This corner is located by GPS measurement

Corner History:

6-11-1870 Robert Perry, County Surveyor, (Book A, Pages 126-127, Survey No. 159) set oak stake at intersecting quarter lines. RPs - 3" Oak S64-1/2°W 40 links (26.40') and Oak Fence Post S15-1/2°W 5 links (3.30'). 1/16th North set oak post at government prorated measure of 19.85 chains (1310.10') then 19.70 chains (1300.20') to North 1/4. 1/16th South set oak post midway and on line at 20.00 chains (1320.00') to South 1/4. 1/16th East set oak post midway and on line at 19.95 chains (1316.70') to East 1/4. RP - 5" Oak S43°E 57 links (37.62'). 1/16th West set oak post at government prorated measure of 19.86 chains (1310.76') then 19.12-1/2 chains (1262.25') to West 1/4. 1/16th Center of SE 1/4 set oak post at intersecting sixteenth lines.

1-23-1871 Robert Perry, County Surveyor, (Book A, Page 144, Survey No. 170) 1/16 West found stake.

10-17-1884 Thomas Hunter, County Surveyor, (Book A, Pages 393-394, Survey No. 384 & Old Field Book No. 14, Page 27) found stone in mound and pits.

4-5-1894 William Fraser, County Surveyor, (Book A, Page 545, Survey No. 505) found stone and mound. 1/16th South set stone midway and on line at 20.07-1/2 chains (1324.95') to South 1/4. 1/16th West set stone and stake on line at government prorated measure of 19.88 chains (1312.08') then 19.10 chains (1260.60') to West 1/4. 1/16th Center of SW 1/4 set stake midway and on line on north-south sixteenth line.

5-19-1966 John Kerr, County Surveyor, (Kerr Field Book No. 92, Page 49) dug extensively in area of corner post and found remains of old fence post and oak stake. Set Cast Iron Monument over 5/8"x12" rod with iron plate and stones at bottom at location best fitting line and chainage. The corner falls 1' east of corner post. 1/16th West found stone and set 3/4" pipe.

10-19-1989 Vince Fangman found Cast Iron Monument to be 2.7' east and 0.03' north of the intersection of quarter lines. Removed Cast Iron Monument and reset at intersecting quarter lines.

6-4-1993 Vince Fangman used computed center at intersecting quarter lines.

5-5-2002 Vince Fangman used computed center at intersecting quarter lines.

9-19-2002 Vince Fangman found and used Cast Iron Monument at intersecting quarter lines.

7-21-2006 County Survey Crew found Cast Iron Monument up 0.2' in good condition. The monument falls 1' west of wooden corner post for fences north-east-west.

10-2-2006 County Survey Crew found Cast Iron Monument at the surface in good condition and measured its position using GPS.

12-15-2006 Fangman Land Surveying found and used Cast Iron Monument at intersecting quarter lines.

10-18-2010 Joel Thoreson, County Surveyor, recommends using the computed intersection of quarter lines for the center of section. Based on the county's section breakdown, the Cast Iron Monument, as located by GPS in 2006, falls 0.26' south and 0.03' west of the computed center.

2-20-2017 Massey Land Surveying found and used Cast Iron Monument.

4-11-2018 Massey Land Surveying used computed center at intersecting quarter lines.