Certificate of Location of Government Corner

ID#: 650704 **Description:** 1/4 SEC 7 18 65 **Date Set:** 7/17/1969 **County:** Olmsted

Section: 07 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1' east of fence south, 1' south of fence west and 1' SE of CP
Post w/sign 2' south
This corner is located by GPS measurement

Corner History:

6-1854 Michael Karrick 32.35 creek 7 lks wide runs NE. 39.15 set quarter section post in mound with trench, pits, charred stake and Osage Orange seeds NE and SW.

5-1893 W.Fraser (P.508 No.477) corner gone. Set boulder stone on section line at prop distances according to gov't notes. 1/16 East set boulder stone M&L 19.95 5/8. 1/16 West set boulder stone at 19.95 5/8 then 19.10 5/8 to sec. cor. 1/16 South drove stake M&L 19.93 1/2 to center 18 stone 4 x 12 x 12. 1/16 center NW 1/4 18 set 2 boulders at inters lines.

5-1930 J.Kerr (B.3 P.30) stone at fence corner. Set 1/16 stake 1261.55 East of SW corner 7. Meas of line North from above 1/16 stake to 1/16 stake on E-W 1/4 line 7 2637.55.

7-16-1969 J.Kerr found 1/16 boulder, glass, old wood post remains and drag tooth by stone, 4' deep just West of corner post fence E and South. Set 1/2" x 3' rod riser 6" West of RR tie corner post.

7-17-1969 J. Kerr found original boulder one foot SE corner post of fences W-S-N. Set CIM over 1" x 10" reinf bar with alum and steel pieces at bottom and orig stone .8' S and .5' East.

2-8-2005 County Surveyor found CIM down 1.8' in good condition.

10-2-2006 County Surveyor found CIM down 1.6' in good condition. Set post with sign south 2.0'.