Certificate of Location of Government Corner

ID#: 650709 **Description:** SEC CEN 7 65 **Date Set:** 9/16/1970 **County:** Olmsted

Section: 07 **Township:** 106N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
Cast Iron Monument

Reference Ties:

The corner falls in centerline of E-W twp road and 53' east of east line of PP
Bottle cap in NE side PP #8628 ESE 91.75'
Bottle cap in N side 4" cedar brace post WSW 69.6'
This corner is located by GPS measurement

Corner History:

7-1910 C. Larson (P.134B) evidently used center of some kind. Meas North on plat 39.76. West set iron stake 1' long likely 9.99 1/2 West of center then 9.99 1/2 then 19.16 to W 1/4 7. Stone found set other corner in NW 1/4 7. Center NW 1/4 and 1/64 corners North and East of this center all stakes.

1930 J. Kerr found this stone in 1930 and he placed junk items around it, glass and many small stones. County Surveyor found stone and placed 5/8"x16" rod on E. side of stone and placed cast iron monu. over
the stone, and left all junk items in hole.

9-16-1970 County Surveyor dug and found stone by J. Kerr in 1930 about 2' deep. Stone is a hard straight sided blue granite 8x14x22. Set CIM over stone.

9-12-1991 V. Fangman found and used CIM for survey in NW 1/4 section 7.

9-15-1995 V. Fangman found and used CIM for survey in north half of section 7.

6-27-2002 V. Fangman found and used CIM for survey in SW 1/4.

7-13-2006 County Surveyor found CIM in good condition down 0.4'.

10-2-2006 County Surveyor found CIM down 0.4' in good condition.

4-25-2008 V. Fangman used computed center at intersecting quarter lines.