Certificate of Location of Government Corner

ID#: 650905 **Description:** SEC COR 8 9 16 17 65 **Date Set:** 5/13/1977 **County:** Olmsted

Section: 09 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1-1/2' east of fence north and in line with fence east
Spike in south side PP #40189 E 4.93'
This corner is located by GPS measurement

Corner History:

6-7-1854 Michael G. Karrick, Deputy Surveyor, measured north 80.00 chains between Sections 16 and 17. Set post for corner to Sections 8, 9, 16 and 17. Erected mound with trench, pits, charred stake, and Osage Orange seeds at each angle.

1-14-1870 Robert Perry, County Surveyor, (Book A, Page 90, Survey No. 134), found old mound and pits and hole where the old post was. Set 8"x15"x21" boulder. 1/16th South set oak stake midway and on line. 1/16th East set red cedar post with 3"x13"x24" stone on south side midway and on line.

5-21-1873 Thomas Hunter, County Surveyor, (Book A, Page 225, Survey No. 228), found stone boulder. 1/16th North set stake midway and on line at 19.98 chains (1318.68'). 1/16th East set stake midway and on line at 19.89-1/2 chains (1313.07').

5-29-1893 William Fraser, Deputy County Surveyor, (Book A, Page 510, Survey No. 478), found stone boulder.

5-13-1977 County Survey Crew dug around the corner post and found black mark extending well down into clay. Accepted black mark as location of Robert Perry's stone. Set Cast Iron Monument over 3/4"x15" rod at black mark location. The corner falls 1-1/2' east of fence north and in line with fence east. RP - Spike in south side PP #40189 E 4.93'.

7-2-2002 County Survey Crew found Cast Iron Monument in good condition and measured its position using GPS.