Certificate of Location of Government Corner

ID#: 651104 **Description:** 1/4 SEC COR 11 14 65 **Date Set:** 6/29/1978 **County:** Olmsted

Section: 11 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 5' south of centerline of E-W twp road and in line with fence north
This corner is located by GPS measurement

Corner History:

6-1854 Gov't Notes M.G. Karrick, Deputy Surveyor West on true line between sections 11 and 14. 40.00 chs. Set quarter section post in mound with trench and pits and charred stake and planted Osage orange seeds N.E. and S.W. 80.00 chs. To section corner.

8-1856 Thomas Hunter, County Surveyor, (Book A P.15 No.23) surveyed the S.E. 1/4 Sec. 11 and the S.W. 1/4 Sec. 12. He set the 1/16th North of 1/4 Cor. 11-14 midway (19.77 chs.) and on line to the Center 11 and measured East 39.55 chains to Sec. Cor. 11-12-13-14.

4-1911 Charles Larson (Book B P.154) set a stone at the 1/16th East and a stone at the 1/16th West of 1/4 Cor. 11-14 but does not mention finding or setting 1/4 Cor. 11-14.

7-27-1976 County Surveyor set a C.I.M. at double the line and measure of the 1/16th West found in 1972.

Correction of a Corner: The correct corner is 10.28' South and 29.19' West of the corner set in 1976 (removed).

5-15-1978 County Surveyor dug again in line with the fence North. Found the remaining 8" of an old stake down 2' in the road and extending into clay.

6-29-1978 County Survyor removed the C.I.M. set in 1976 and reset it over a 1/2"x21" rod at the location of the stake found.

2-1-2005 County Surveyor found CIM down 0.8' in good condition.

7-14-2006 County Surveyor found CIM down 0.8' in good condition.