Certificate of Location of Government Corner

ID#: 651204 **Description:** 1/4 SEC COR 12 13 65 **Date Set:** 6/28/1978 **County:** Olmsted

Section: 12 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 4' south of centerline of E-W twp road and in line with fence north
Spike in W side 6" Chinese Elm N 31.23'
Spike in E side PP #8094 S 25.95'
County Survey Disk in NW side 6" Pine SW 73.56'
This corner is located by GPS measurement

Corner History:

6-1854 Gov't Notes M.G. Karrick, Deputy Surveyor West on true line between sections 12 and 13. 40.00 chs. Set quarter section post in mound with trench and pits and charred stakes and planted Osage Orange seeds N.E. and S.W. 80.00 chs. To section corner.

8-1856 Thomas Hunter, County Surveyor, (Book A P.15 No.23) used the corner to set the 1/16th West and the Center 12.

12-1857 Thomas Hunter (Book A P.40 No.62) used the corner to set the 1/16th North.

6-1870 Robert Perry, County Surveyor, (Book A P.124 No.158) found the 1/16th North and used it to reset the Center 12.

5-1-1978 County Surveyor dug from a point in the center of the road and in line with the fence North for 8' North, 10' South, 7' East, and 7' West, but did not find anything. We also dug at the 1/16th West and the Center 12 but did not find anything.

6-28-1978 County Surveyor set a C.I.M. over a 5/8"x19" rod midway between the S.E. Cor. 12 and S.W. Cor. 12 and at double the measure from the calculated Center 12 over the fence East at the 1/16th South. The corner came 4' south of the center of the E-W road and in line with the fence north.

11-8-2002 County Surveyor found CIM in good condition.