Certificate of Location of Government Corner

ID#: 651209 **Description:** SEC CEN 12 65 **Date Set:** **County:** Olmsted

Section: 12 **Township:** 106N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
5/8" iron rod

Reference Ties:

The monument is up 0.3'
Large boulder on west side

Corner History:

8-12-1856 T. Hunter (P.15 No.23) SE 1/4 11 SW 1/4 12 used or set corner. 1/16 West set M&L 19.81.

9-10-1857 T. Hunter (P.40 No.62) 1/16 South set M&L 19.68 6-7 106-14. Bearing tree N 56° W 1.09 N 19° E .84. 1/16 East set M&L 19.94. 1/16 center SE 1/4 12 M&L 19.93 on E-W 1/16 line N89 1/4 W. 19.76 North to 1/16 cor. on E-W 1/4 line N 5' E. BT N 40 1/2° W .14 N 44 1/2° E .29.

6-8-1870 R. Perry (P.124 No.158) set marked stake. BT 12" Oak N 85 1/2 E .87 1/2. Marked and blazed 1/16 West reset 1/16 corner correctly formerly set P.119. The stake at center also correction of P.119. B tree then 12" Oak N 82 1/2 E .98 (64.68) this stake found P.119. 1/16 corner in P.119 West M&L 19.77 now different but doesn't say what tree 4" oak N 14 1/2 E 1.02 1/2 formerly N 26° E 1.12.

5-4-1978 County Surveyor dug from the 5/8" rod (found on the East side of the corner post and used as a t.p.) 2' N, 3' E, 3' S and 4' W by 1 1/2' deep to clay. Found nothing, set rod back.

4-12-1996 V. Fangman used computed center.

8-20-1996 V. Fangman used computed center at intersecting quarter lines.

3-8-2004 Massey Land Surveying used computed center at intersecting quarter lines.

4-14-2004 Massey Land Surveying used computed center at intersecting quarter lines.

4-13-2007 V. Fangman used computed center at intersecting quarter lines.

2-6-2012 County survey crew found 5/8" rod in good condition.