Certificate of Location of Government Corner

ID#: 651505 **Description:** SEC COR 15 16 21 22 65 **Date Set:** **County:** Olmsted

Section: 15 **Township:** 106N **Range:** 15W **Monument Description:** Coordinate Position

Reference Ties:

This corner is located by GPS measurement

Corner History:

6-6-1854 Michael G. Karrick, Deputy Surveyor, measured north 80.00 chains between Sections 21 and 22. Set post for corner to Sections 15, 16, 21 & 22. Erected mound with trench, pits, charred stake and Osage Orange seeds at each angle.

1-14-1870 Robert Perry, County Surveyor, (Book A, Page 90, Survey No. 134), found original stake in mound with NE & NW pits plain. Set 4"x11"x23" stone. 1/16th West set 10"x10"x29" stone midway and on line.

3-24-1895 William Fraser, County Surveyor, (Book A, Page 618, Survey No. 561), found corner set by Robert Perry. 1/16th West found corner set by Robert Perry. 1/16th South set small stake midway and on line at 19.93 chains (1315.38').

6-12-1935 John Kerr, County Surveyor, (Kerr Field Book No. 10, Page 5), found stone 1-1/2' south of corner post.

7-5-1972 Roger Brand, County Surveyor, found 4"x11"x23" limestone. Set Cast Iron Monument over 1/2"x24" rod at stone location. Set stone on west of Cast Iron Monument. Steel post on north side of Cast Iron Monument.

2-28-1992 Vince Fangman found Cast Iron Monument removed by tillage. 1/2" rod still in place.

2-17-2010 County Survey Crew found 1/2" rod down 1.4' in good condition and measured its position using GPS. Landowner (DeCook) mentioned that the monument will soon be destroyed by expansion of the adjacent quarry.

2017 Monument location destroyed by quarry expansion. The Olmsted County Coordinates (NAD83 '96 Adj.) of the 1/2" rod location is North=152868.1689 and E=578569.4248.