Certificate of Location of Government Corner

ID#: 651604 **Description:** 1/4 SEC COR 16 21 65 **Date Set:** 12/11/1975 **County:** Olmsted

Section: 16 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 5-1/2' south of east-west fence and in line with fence north
The monument is down 0.3'
Post w/sign 2' north
This corner is located by GPS measurement

Corner History:

6-7-1854 Michael G. Karrick, Deputy Surveyor, measured west 40.00 chains on true line between Sections 16 and 21. Set quarter section post in brush. Erected mound with trench, pits, charred stake, and Osage Orange seeds NE and SW.

1-14-1870 Robert Perry, County Surveyor, (Book A, Page 90, Survey No. 134), found original stake in mound and pits plain. Set 6"x13"x32" stone. 1/16th East set 10"x10"x29" stone midway and on line. 1/16th West set red cedar post midway and on line.

3-24-1895 William Fraser, County Surveyor, (Book A, Page 618, Survey No. 561), found corner as set by Robert Perry. 1/16th East found corner as set by Robert Perry.

12-11-1975 County Survey Crew found remaining 2' of recorded stone. Dug out stone and set Cast Iron Monument over 1/2"x18" rod at stone location. Set a 16" piece broken from stone on north side. The corner falls 5-1/2' south of east-west fence and 2' east of fence north. RPs - Nail in east side 18" Elm NNW 9.57', Nail in north side dead twin elms E 47.0', Nail in south side 22" elm SE 88.6', Nail in east side 36" Box Elder S 34.65'.

3-14-1977 County Survey Crew found Cast Iron Monument.

2-17-2010 County Survey Crew found Cast Iron Monument down 0.3' in good condition and measured its position using GPS. All ties gone. Set post w/sign 2' north.