Certificate of Location of Government Corner

ID#: 651605 **Description:** SEC COR 16 17 20 21 65 **Date Set:** 4/24/2012 **County:** Olmsted

Section: 16 **Township:** 106N **Range:** 15W **Monument Description:** Cast iron Cap on Telspar Pipe

Reference Ties:

The monument is up 0.4
The corner falls in line with N-S power line
Post w/sign 2' south
This corner is located by GPS measurement

Corner History:

6-1854 Michael Karrick 68.40 creek 20 lks wide runs NE. 80.00 set post for corner to sections 16,17,20 & 21. Elm 20 S 64 W 35. Elm 18 N 48 W 30. Elm 17 N 48 E 49. Elm 10 S 63 E 68.

1-1870 R. Perry (P.90 No.134) relocated section corner from 2 standing bearing trees and 2 bearing stumps. Set 4" square red cedar post. 1/16 East set 4 x 4 x 40 red dedar post M&L. 1/16 North set oak stake marked.

1-1891 Thos Fraser (P.449 No.433) found cedar stake set by R. Perry.

5-1893 W.Fraser (P.510 No.478) found red cedar stake P.90. 1/16 North could not find stake, set big stone M&L 19.98. 1/16 West meas 39.81-1/2 to 8 x 12 x 25 stone set M&L . Near center SE 1/4 17 set stone at 22.15-1/2 (1462.23) then 885-1/2 (584.43) stake then 885-1/2.

7-1911 C.Larson (P.160B) found cedar post. Meas West 39.81', meas South 39.82'.

4-1933 J.Kerr (B.8 P.63 S.20) found cedar post.

1-20-1968 Sankstone found remains of cedar stake drove iron marked conservation. 30d spike in 36" Elm SW 58.7' of old red cedar stake. 30d spike in 12" Ash ESE 55.6' also found 1/16 stone North.

1977 County Surveyor corner now on east side of new corner post. Corner post now gone.

4-24-2002 County Surveyor found conservation pin at surface in line with power lines that run N-S. Set sign and post 2.0' South.

5-19-2005 V. Fangman found and used MN conservation marker as corner for survey in NE 1/4 section 20.

4-24-2012 County survey crew found 1"x20" rod with 2 1/2" cap marked Minnesota Conservation Dept. in good condition. Removed and replaced with a 5' telspar pipe with cast iron cap.