Certificate of Location of Government Corner

ID#: 651705 **Description:** SEC COR 17 18 19 20 65 **Date Set:** 7/15/69 **County:** Olmsted

Section: 17 **Township:** 106N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1 1/2' west of N-S fence
Bottle cap in PP #8525 N 48.0'
This corner is located by GPS measurement

Corner History:

6-1854 Michael Karrick 80.00 set post for corner to sections 17,18,19 and 20. Erected mound with trench pits, charred stake and Osage Orange seeds at each angle.

5-1898 W.Fraser (P.508 No.477) found stake in mound. Center set stone in place of stake 8 x 14 x 24. 1/16 North set boulder M&L 19.97.

5-30-1898 W.Fraser (P.510 No.478) found stone P.508. 1/16 East drove stake M&L 19.90-3/4. 1/16 North stone on plat M&L 19.97.

4-1933 J.Kerr (B.8 P.63) may or may not have found and used corner. Meas South marked on plat 2929.75.

7-14-1969 J.Kerr meas from 1/16 fence North running West. Found stone exactly 8 x 14 x 24. 1.3' West of N-S fence, no E-W fences. Meas 1324 from nail in line fence West 7-15 dug out stone set CIM over 3/4" x 8" reinf rod with glass and many short pieces of iron from brisie clipper. Placed original stone about 1' North and slightly lower than top of CIM, 4' down. Put 4 or 5 stones at bottom of CIM with inner part of thermos near top CIM. RP: Power pole # 8525 in fence North 48.0' bottle cap. 16 North dug 3 hours for stone on estin line and meas R 1318.0, con't line and meas to fence line East at 7-8-17-18. 5263.35 less .5' for off line meas R 5272.1.

4-15-2002 County Surveyor found CIM down 1.1' in good condition.