Certificate of Location of Government Corner

ID#: 652009 **Description:** SEC CEN 20 65 **Date Set:** 2/25/1992 **County:** Olmsted

Section: 20 **Township:** 106N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
1/2" pipe w/cap RLS #14888

Reference Ties:

The corner falls 3' south of large steel pipe fence post
This corner is located by GPS reference stations "652106 & Blacksmith"

Corner History:

3-14-1860 Samuel McDowell (P.64 No.90) shows center sec. He surveyed the SW 1/4 of sec 20 & West 1/2 of sec 29.

4-1933 J.Kerr (B.8 P.63) run N-S 1/4 line from true corners. Run E-W 1/4 line from true corners. May have set steel fence post as corner. Meas North 2626.2. Meas South 2636.8. Meas East 2622.0. Meas West 2604.25.

12-6-1986 McGhie & Betts used computed center at intersecting quarter lines.

10-21-1987 V. Fangman used computed center at intersecting quarter lines.

11-11-1991 V. Fangman found and used 3/4" pipe at center of section.

2-25-1992 V. Fangman set 1/2" pipe w/cap #14888 at intersecting quarter lines.

7-13-1999 V. Fangman found and used 1/2" pipe at center of section.

10-27-1999 V. Fangman found and used 1/2" pipe at center of section.

11-12-1999 V. Fangman found and used 1/2" pipe at center of section.

12-22-1999 V. Fangman found and used 1/2" pipe at center of section.

5-10-2002 County Surveyor found 1/2" pipe in good condition.